



Wireless presentation HDMI dongle

The wireless presentation dongle allows to share content (e.g. videos, applications) from your computer to an iiyama 42-series LFD with the EShare app pre-installed. It is compatible with computers equipped with HDMI (version 1.4) and USB outputs and supports smooth video streaming up to 1080p.

To use the dongle, you also need the [EW-7811UTC](#) wireless dual-band mini USB adapter connected to the LFD. You can buy it separately or choose the [KIT](#) version which contains both products.

01 DEVICE

| | |
|--------------------------------|---|
| Supported platforms | Windows, MAC, Chrome, any OS supporting HDMI standard 1.4 |
| HDMI Out | x1 |
| Audio | stereo, radio quality 16bits 48kHz |
| Frame rate | up to 60 fps depending on environment (FHD) |
| Output resolution | 720x480, 720x576, 1280x720, 1920x1080 |
| Input resolution | Video: 480p, 576p, 720p, 1080p PC timing: 640x480, 800x600, 1024x768, 1280x720, 1920x1080 |
| Wireless | IEEE 802.11ac, 5GHz, IEEE 802.11n, 2.4GHz |
| Data rate wireless | up to 867Mbps |
| Authentication protocol | WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise) |
| Security (encryption) | WPA2 |
| Reach | 15 m max. |

02 POWER MANAGEMENT

| | |
|--------------------|--------------|
| Power usage | 2.5W typical |
|--------------------|--------------|

03 SUSTAINABILITY

| | |
|--------------------|------------------|
| Regulations | CE, RoHS support |
|--------------------|------------------|

04 DIMENSIONS / WEIGHT

| | |
|-----------------|---------------|
| EAN code | 4948570032501 |
|-----------------|---------------|

05 ENVIRONMENTAL CONDITIONS

| | |
|-----------------------------|---------------|
| Operation temperature range | 0°C - 40°C |
| Operation humidity | 10% - 80% |
| Storage temperature range | - 10°C - 60°C |
| Storage humidity | 5% - 90% |

06 RELATED INFORMATION

Related products [EW-7811UTC](#), [WP D001HU KIT](#)

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IYAMA CORPORATION. ALL RIGHTS RESERVED