



An Intel® i5 slot PC with Windows® 10 IoT Enterprise

This mini PC with Intel® Core™ i5 inside turns your iiyama interactive large format display into a stand-alone solution. It comes equipped with a powerful Intel® processor with integrated Ultra HD graphics and a fast SSD drive. No hassle with cables and having to mount a PC at the back of the monitor or on a floor lift. Simply slide in the iiyama slot PC and get started right away.

The module is only compatible with the iiyama TExx03MIS and TExx04MIS* Series; 55": [TE5503MIS-B1AG](#) / [TE5503MIS-B2AG](#), 65": [TE6503MIS-B1AG](#) / [TE6504MIS-B1AG](#) / [TE6504MIS-B2AG](#) , 75": [TE7503MIS-B1AG](#) / [TE7504MIS-B1AG](#) / [TE7504MIS-B2AG](#), 86": [TE8603MIS-B1AG](#) / [TE8604MIS-B1AG](#) / [TE8604MIS-B2AG](#), 98": [TE9803MIS-B1AG](#)

*Excluding the 98" [ProLite TE9804MIS-B1AG](#)

01 DEVICE

| | |
|------------------|---|
| Type | slot PC |
| CPU | Intel® Core™ i5-8400 |
| RAM | 8GB DDR4 |
| SSD | 256GB M.2 |
| Graphics | Intel® HD Graphics 630 |
| Chipset | Intel® H310 |
| Sound card | Integrated High Definition Audio Stereo |
| Networking | 10/100/1000M Adapter |
| WiFi | 802.11ac (2.4GHz/5GHz) |
| Bluetooth | 4.2 |
| Operating system | Win 10 IoT Enterprise 64-bit |
| LAN (RJ45) | x1 |
| USB | 3.0 x4, 2.0 x2, 3.1 Type C x1 |
| VGA Out | x1 |
| DisplayPort Out | x1 |
| HDMI Out | x1 |
| Microphone In | x1 |

02 POWER-MANAGEMENT

| | |
|-----------------|------------------------------|
| Napájecí zdroj: | interní |
| Napájení | AC 100 - 240V, 50/60Hz |
| Odběr energie: | 95W typisch, 1.35W odpočinek |

03 ROZMĚRY / HMOTNOST

| | |
|---------------------------|------------------------|
| Rozměry výrobku Š x V x D | 263.4 x 32.2 x 246.1mm |
| Rozměry balení Š x V x D | 312 x 91 x 353mm |
| Váha (bez balení) | 1.9kg |
| EAN code | 4948570032723 |

04 ENVIRONMENTAL CONDITIONS

| | |
|-------------------------|---------------|
| Rozsah provozní teploty | 0°C - 45°C |
| Operation humidity | 10% - 90% |
| Rozsah teploty v klidu | - 20°C - 60°C |
| Storage humidity | 10% - 90% |

Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.

© IYAMA CORPORATION. ALL RIGHTS RESERVED