

UNIFIED COMMUNICATIONS



BİLGİLER

4K 120D FOV Konferans web kamerası



120° görüş alanıyla, 2D ve 3D gürültü giderme teknolojilerine sahip 8 mega piksel UC CAM120UL, düşük ışık koşullarında bile olağanüstü pürüzsüzlük ve ayrıntı sunar ve önemli olan her şeyin kamerada kalmasını sağlar. Entegre 2 mikrofon dizisi, sesi 4 metreye kadar uzaktan algılar.

Kurulumu kolay ve 10 derecelik açı ayarıyla 360 derecelik yatay dönüşü destekleyen bu hafif kamera, Zoom, Skype, Microsoft Teams ve daha fazlası gibi tüm önde gelen konferans yazılımlarını desteklerken büyük veya küçük her ortamda çalışır.




120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.



2D & 3D Digital Noise Reduction with HDR

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos, even in low light conditions. And to make sure everyone from your team is always clearly visible, regardless of the ambient lighting conditions, the high dynamic range (HDR) technology automatically adjusts brightness level to keep you in the spotlight.



Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.



ÖZELLİKLER

01 KAMERA

Piksel	8M
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Çapraz görüş alanı (dFoV)	120°
Odak modu	fixed
Odak mesafesi	1.5m
Diyafram	1.8

02 SES

Mikrofon dizisi sayısı	2
Ses alma mesafesi	4m
Ses alma açısı	180°

03 MEKANİK

Eğim açısı	≤10°
Döndürme	360°

04 ÖLÇÜLER / AĞIRLIK

Ürün boyutları G x Y x D	118 x 53.4 x 48.5mm
Kutu boyutları G x Y x D	147 x 91 x 70.5mm
Ağırlık (kutu hariç)	0.2kg
Ağırlık (kutu ile birlikte)	0.31kg
EAN kodu	4948570033010

05 İLGİLİ BİLGİ

İlgili ürünler [UC CAM120ULB-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01M](#)



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED